



RECOMMENDED PCB LAYOUT

NOTE:
 MATERIAL:
 HOUSING:PBT+30%G.F UL 94V-0
 CONTACT:BRASS
 SHELL:SPCC
 PLATING:
 CONTACT: GOLD AND TIN OVER NICKEL PLATING
 SHELL: NICKEL OVER ALL PLATING
 SPECIFICATION:
 CURRENT-MAX[AMPS]1.5A
 VOLTAGE-MAX[VOLTS]:30V
 WITHSTANDING VOLTAGE:500V AC
 CONTACT RESISTANCE[OHMS]:30MΩ MIN
 INSULATION RESISTANCE[OHMS]:1000MΩ MIN
 INSULATION COLOR:WHITE
 ENVIRONMENTAL:
 TEMPERATURE RANGE:-40°C TO+105°C
 PART NO.:

08/09/26	SYSTEM		變更尺寸	△	A1				
08/05/27	SYSTEM		NEW DWG		A0				
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.				
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差參考表			CnC Tech,LLC TITLE: USB 4P A/M SMT H=6.00mm 成品針長2.25mm						
X.X	±0.30	X.X°				±3.00°	APPD:	PRODUCT NO: 1002-016-01101	
X.XX	±0.15	X.XX°	±1.00°	CHECK:	DATE	SCALE	UNIT	TYPE	PAGE
X.XXX	±0.100	X.XXX°	±0.500°	DRAW:	2008.09.26	1:1	mm	CD	1/1