


Material: UL94 V-2 Nylon 6/6	
Color: Natural	
Part No.	A
	mm in
CBRLDS405A	2.5 .098
CBRLDS410A	3.2 .126
CBRLDS415A	4 .157
CBRLDS420A	5 .197
CBRLDS425A	6 .236
CBRLDS430A	7 .276
CBRLDS435A	8 .315
CBRLDS440A	9 .354
CBRLDS445A	10 .394
CBRLDS450A	12 .472
CBRLDS455A	14 .551
CBRLDS460A	16 .630

TO SNAP LOCK IN A 3 (.118) Ø HOLE, IN A  
1.6 (.062) PANEL THICKNESS



TO SNAP LOCK IN A 4 (.157) Ø HOLE, IN A  
0.8 - 1.6 (.031 - .062) PANEL THICKNESS

TOLERANCES  
UNLESS NOTED  
≤ 5 mm ±0.2  
5 - 20 mm ±0.3  
20 - 40 mm ±0.4  
40 - 60 mm ±0.5  
60 - 100 mm ±0.8  
≥ 100 mm ±1.0

TITLE: DUAL LOCKING CIRCUIT BOARD SUPPORT		DWG IN MM (IN)	
FILE# CBR LDS4XX	SHEET: 1 OF 1	SHEET SIZE: A	DT: 01/08/15
RE:	PART #		PRINT TYPE
ESSENTRA COMPONENTS		SEE TABLE CA	