

Maxi free-standing Beacons / EvoSIGNAL

**Maxi TwinLIGHT 12/24VAC/DC RD**



|           |                |
|-----------|----------------|
| Part No.: | 262.110.70     |
| Series:   | EvoSIGNAL Maxi |



**MECHANICAL DATA**

|                              |                             |
|------------------------------|-----------------------------|
| Height                       | 173 mm                      |
| Diameter                     | 120 mm                      |
| Materials                    | PC<br>PC/ABS                |
| Dome colour                  | Red                         |
| Housing colour               | Grey                        |
| Protection category          | IP66                        |
| Connection                   | Push-in terminal            |
| cross-sectional area minimum | 0,25mm <sup>2</sup> / 24AWG |
| cross-sectional area maximum | 1,50mm <sup>2</sup> / 16AWG |
| Working temperature minimum  | -30°C                       |
| Working temperature maximum  | +60°C                       |
| Weight with packaging        | 496 g                       |
| Product weight               | 346 g                       |

**ELECTRICAL DATA**

|                             |                    |
|-----------------------------|--------------------|
| Operating voltage           | 12V<br>24V         |
| Operating voltage type      | AC/DC              |
| Operating voltage frequency | 50Hz               |
| Operating voltage tolerance | +/- 10%            |
| Rated operational voltage   | 24 VDC             |
| Rated operational current   | 700 mA             |
| Rated inrush current        | <1800 mA           |
| Protection class            | Protection class 2 |
| Pollution degree            | 3                  |
| Overvoltage category        | III                |

**OPTICAL DATA**

|                              |                                 |
|------------------------------|---------------------------------|
| Light source                 | LED                             |
| Light colour                 | Red                             |
| Optical signal image         | Blink<br>Permanent<br>TwinLight |
| Blink frequency (Hz)         | 1 Hz                            |
| Service life optical         | 50,000 h minimum                |
| Pulse- & pause Duration [ms] | 484ON, 480OFF                   |

**APPROVAL DATA**


|                  |     |
|------------------|-----|
| Conforms with CE | Yes |
|------------------|-----|

! For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

Maxi free-standing Beacons / EvoSIGNAL  
**Maxi TwinLIGHT 12/24VAC/DC RD**

|                               |                       |
|-------------------------------|-----------------------|
| WEEE                          | Yes                   |
| Conform with ATEX-directive   | No                    |
| Conforms with CCC             | No                    |
| Conforms with UL              | cULus                 |
| UL Type Rating                | Type 12               |
| Conforms with FCC             | No                    |
| Conforms with IC              | No                    |
| EAC certificate available     | Yes                   |
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with AS-I            | No                    |
| ICAO Certification            | No                    |
| Conforms with GL              | No                    |
| Conforms with RoHS CN         | No                    |
| Conforms with VdS             | No                    |

**DRAWING**



**!** For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.