


KombiSIGN 40 / ClassicLOOK
TwinFLASH Classic 24VDC BU


| | |
|-----------|--------------|
| Part No.: | 634.520.55 |
| Series: | KombiSIGN 40 |

**MECHANICAL DATA**

| | |
|-----------------------------|---------------|
| Height | 59 mm |
| Diameter | 40 mm |
| Materials | PC |
| Dome colour | Blue |
| Protection category | IP66 IP69K |
| Working temperature minimum | -30°C |
| Working temperature maximum | +60°C |
| Weight with packaging | 39 g |
| Product weight | 29 g |

ELECTRICAL DATA

| | |
|-----------------------------|--------------------|
| Operating voltage | 24V |
| Operating voltage type | DC |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 65 mA |
| Rated inrush current | 500 mA |
| Protection class | Protection class 3 |
| Pollution degree | 3 |
| Request to external PSU | SELV/PELV |

OPTICAL DATA

| | |
|----------------------|------------------|
| Light source | LED |
| Light colour | Blue |
| Optical signal image | TwinFlash |
| Flash frequency | 1 Hz |
| Service life optical | 50,000 h maximum |

APPROVAL DATA

| | |
|-----------------------------|---------|
| Conforms with CE | Yes |
| WEEE | Yes |
| Conforms with RED directive | No |
| Conform with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| UL Type Rating | Type 12 |
| Conforms with FCC | No |
| Conforms with IC | No |




For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

KombiSIGN 40 / ClassicLOOK
TwinFLASH Classic 24VDC BU

| | |
|---------------------------|-----|
| EAC certificate available | Yes |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with GL | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |

DRAWING



! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.