## Completely pre-assembled Signal Towers / KOMPAKT 37 K37 cable EM Pulse tone 12VAC/DC YE/RD



i

MECHANICAL DATA Height	<b>Е конза</b> с <b>Шиз</b> ЦК 141 mm
Height	
-	
	00
Diameter	38 mm
Materials	PC
Dome colour	Red
	Yellow
Housing colour	Black
Protection category	IP65
Connection	Cable
cross-sectional area maximum	0,34mm² / 22AWG
Cable entry	Membrane grommet
Cable entry minimum	d = 1 mm
Cable entry maximum	d = 9 mm
Cable length	2000 mm
Tension relief	Pull-out protection
Type of fixing	Built-in mounting
Working temperature minimum	-20°C
Working temperature maximum	+50°C
Weight with packaging	90 g
Product weight	90 g
ELECTRICAL DATA	
Operating voltage	12V
Operating voltage type	AC/DC
Operating voltage frequency	50Hz
Operating voltage tolerance	+/- 10%
Rated operational voltage	12 VDC
Rated operational current	225 mA
Rated inrush current	500 mA
Protection class	Protection class 2
Pollution degree	3
	In the connection area: 2
OPTICAL DATA	
Light source	LED
Light colour	Red Yellow
Optical signal image	Permanent
Service life optical	50,000 h maximum
ACUSTICAL DATA	

## ACUSTICAL DATA

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

i




## Completely pre-assembled Signal Towers / KOMPAKT 37 K37 cable EM Pulse tone 12VAC/DC YE/RD

80,0 dB (A)	
Pulse tone	
2900 Hz	
5,000 h minimum	
APPROVAL DATA	
Yes	
Yes	
No	
No	
No	
cULus	
Type 12 Type 4X	
No	
No	
Yes	
Yes (WERMA (UK) Ltd.)	
No	

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

i

Completely pre-assembled Signal Towers / KOMPAKT 37 K37 cable EM Pulse tone 12VAC/DC YE/RD



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.